



DELTA® Accessories

For easy installation and ultimate performance.

PREMIUM QUALITY

■ Important details for a perfect installation

■ Compliments the complete range of DELTA® products

■ Designed for fast & easy application, and optimum performance

DELTA® ACCESSORIES

Accessories for DELTA®-MS, DELTA®-MS UNDERSLAB, DELTA®-MS

DELTA®-FAST'ner™

DELTA®-FAST'ner™ is a multi-stud fastener for attaching the DELTA®-MS and DELTA®-DRAIN to the foundation walls. The fastener is used with a concrete nail* to fasten the DELTA® membrane in place. It is made of PE and is orange in color. DELTA®-FAST'ner™ can replace DELTA®-PLUGS.



DELTA®- MS/DELTA®- FAST'ner install

DELTA®-TERMINATION BAR

DELTA®-TERMINATION BAR is a strip used to fasten the flat tab of the DELTA® membrane to the foundation walls, and to stop debris from clogging the "air gap" drainage plane behind the membrane. It is attached with a concrete nail*. DELTA®-TERMINATION BAR is made of PE and is black in color.



DELTA® - MS/DELTA® - TERMINATION BAR install

DELTA®-FLASH

DELTA®-FLASH is a 2.25" wide angle flashing that is used to finish off the top of the flat tab, around windows, and vertical terminations of the DELTA® membrane installations. It is attached with concrete nails*. DELTA®-FLASH is made of PE and is black in color. DELTA®-FLASH can replace the Termination Bar.



DELTA®- MS/DELTA®- FLASH install

DELTA®-SEALANT

DELTA®-SEALANT is a black mastic formulation that is used to seal off the flat tab and overlaps in the membranes during the installation process. The sealant is also used to seal off any gaps in the membrane created at interior and exterior corner installations where a tight fit may not be possible, and to seal off gaps around DELTA®-FLASH, DELTA®-TERMINATION BAR or DELTA®-MOLD STRIP installations.



DELTA®- DRAIN/DELTA®- SEALANT install

CLEAR, DELTA®-DRAIN, DELTA®-DRAIN 000's & DELTA®-FL.

DELTA®-PLUG

DELTA®-PLUG is a single fastener for attaching DELTA® membranes to foundation walls. The plug is used with a concrete nail* to fasten the DELTA® membrane in place. DELTA®-PLUG is made of PE and is brown in color.



DELTA®- DRAIN/DELTA®- PLUG install

DELTA®-MOLD STRIP

DELTA®-MOLD STRIP is a 3" wide molding used to finish off the installation of the DELTA® membrane around windows, doors, or gradient changes in the foundation. It is attached with concrete nails*. DELTA®-MOLD STRIP is made of PE and is black in color.



DELTA® - MS CLEAR/DELTA® - MOLD STRIP install

DELTA®-MOISTURE PROOF TAPE

DELTA®-MOISTURE PROOF TAPE is a polypropylene based sealing product that is extremely resilient to damage from human traffic during installation, and it has a very low vapor permeance value which makes it an excellent vapor retarder. The tape is combined with a very aggressive adhesive that sticks to most materials that are sound, clean and dry. DELTA®-MOISTURE PROOF TAPE is used for seaming DELTA® membranes. The tape comes in a roll size of 2.35 in. x 118 ft.



DELTA® - FL/
DELTA®MOISTURE PROOF TAPE install



DELTA®- DRAIN 6000/
DELTA®MOISTURE PROOF TAPE install

* When installing DELTA®-MS CLEAR replace concrete nails with galvanized screws.

DELTA®

COSELLA DÖRKEN

Cosella-Dörken Products Inc.
4655 Delta Way
Beamsville, Ontario
L0R 1B4
(905) 563-3255
Fax: (905) 563-5582
1-888-4 DELTA 4
info@cosella-dorcken.com
cosella-dorcken.com

A company of the Dörken Group

The information printed in this brochure reflects product information and specifications at the date of printing. The manufacturer reserves the right to make changes when necessary.

DELTA®-branded quality products manufactured by Cosella-Dörken.